

ACCESSORIES

Preheaters



TMT-PH200

SAFE FREE

The TMT-PH200 infrared, board preheater is suitable for leaded and lead free, applications. A sensor controlled feedback loop system with digital display enables easy adjustment of temperature.

- ► Adjustable, easy to use temperature control knob
- ▶ Digital display shows temperature
- Utilizes a quartz infrared heater
- Sensor control feedback loop to control temperature

TMT-PH200 SPECIFICATIONS

Input Line Voltage:	220-240 VAC
Power:	600 Watts
Temperature Range:	100 °C - 380 °C
Heating Area (W x L):	130mm x 130mm
Heating Method:	Infrared
Fuse:	250V 5A
Size (W x H x D):	220mm x 73mm x 250mm
Weight:	2.1 KG

PACKING LIST

TMT-PH200	IR Preheater
-----------	--------------

CERTIFICATION MARK





TMT-PH300

SAFE

LEAD FREE

The TMT-PH300 uses advanced, intelligent, control technology to accurately regulate the temperature of the infrared board preheater. Three heating modes allow the system to manage both leaded and lead free applications.

- ▶ Microprocessor accurately regulates temperature
- ► Two external temperature sensor probes
- Professional board holder allows 3D adjustments
- Three heating modes to meet different requirements

TMT-PH300 SPECIFICATIONS

Input Line Voltage:	TMT-PH300-1	100-110 VAC, 1000 Watts
	TMT-PH300	220-240 VAC, 850 Watts
Temperature Range:		50°C - 400°C
Heating Area (W x L):		200mm x 250mm
Heating Method:		Infrared
Fuse: TN	ИТ-РН300-1	250V 15A
TMT-PH300		250V 8A
Size (W x H x D)	:	260mm x 90mm x 410mm
Weight:		3.8 KG

*Optional: For extra large applications please use the TMT-PH600 preheater.

PACKING LIST

TMT-PH300	IR Preheater
PH-KTC-1	Thermocouples - 2 Pack





